

SkyFIT™ Manual Measuring Instructions

[Link to measuring video](#)

SkyFIT™ manual blinds are designed to fit at the **bottom edge of the recess** of your roof space where the **upstand meets the ceiling**.

YOU MUST MAKE SURE THERE IS ROOM FOR THE BLIND AT THE EDGE OF YOUR RECESS (SEE PRODUCT DIMENSIONS GUIDE & PAGE IN THIS BROCHURE). Make sure the back of the cassette which is 52mm has clearance and there is clearance underneath for the lips of the blind which fit over the edge of the recess.

Measure the **width in 3 places at the bottom edge of the recess**.

We assume that **width 1** is where you are going to fit the **head** of the blind.

Width 2 is the middle of the recess and **width 3 is the foot of the recess**.

Ideally there should not be more than 6mm difference between width 1 and width 2.

Also measure the length in 3 places. We use the shortest length as the length of the blind.

To ensure correct operation and full black out performance the blind can only work within limited window reveal tolerances i.e. the window must be as square as possible, fitting a blind into or on the edge of a window recess outside of the stated tolerances will lead to poor operation, reduced black out performance and or product damage.

Minimum Size: 400mm width x 400mm length

Maximum Size: 1500mm width x 1500mm length

Blinds

Blind #1

Width

width 1 (mm)



width 2 (mm)

width 3 (mm)



Length

length 1 (mm)

length 2 (mm)

length 3 (mm)

